



Pitch Range In mm		Nominal Dimension		Range In mm		Tolerance	
Over	Under	Over	Under	Over	Under	Over	Under
6	10	10	30	60	100	150	0.1/10
T0	10	24	30	60	100	150	≤
±0.15	±0.20	±0.30	±0.30	±0.50	±0.70	±1.00	±1.30
							±2°

ITEM	NAME OF PART	MATERIAL	NOTES
4	COVER	PC	UL94V-2
3	SCERW	STEEL	Ni PLATED
2	PIN HEADER	COPPER ALLOY	Sn PLATED
1	HOUSING	PA66	UL94V-0

UL 标准/UL Standard:		B	C	D
额定电压/Rated Voltage(V)	Current(A)	300/15	150/15	300/10
EC 标准/EC Standard:				
过压类别/Overvoltage Category/污染等级/Pollution Degree		III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)		300/24	300/24	600/24
额定冲击电压(KV)/Rate Impulse Voltage(KV)		5	5	5
额定扭矩/Torque Tightening(N·m/Lb.in)		M3, 0.5/4.43		
线径范围/Wire Range(AWG)		22~14AWG		
间距/Pitch(mm)/线数范围/Poles		8.25/N=02~24P		
剥线长度/Stripping Length(mm)		8		
使用温度范围/Operating temperature(°C)		-40~+105		
符合RoHS环保要求/Conform to RoHS		Yes		

MATERIAL: /
SURFACE: /

MAT NO.: /
STATUS: /

APPD: /
CHKD: /

NAME: **DEGSON** 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: DG338R-C01

TYPE: CUSTOMER DRAWING

SCALE: 2:1

REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6

1/1