



公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)	
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
3	6	10	18	30	50	80	120	180	250	315	400	500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
3	Spring	Stainless steel	/
2	Current carrier	Copper	Sn Platte
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

MATERIAL:	/	SURFACE:	/
MAT NO.:	/		
STATUS:	/		
APPD:	LIGL 2020.05.29	NAME:	WS2.5T-DIN35-01P-1Y-00A(H)
CHKD:	Maou 2020.05.29	DRAWING NO.:	WS2.5T-DIN35-C01
DRAFT:	ZhengQG 2020.05.29	TYPE:	CUSTOMER DRAWING
SIZE:	A4	SCALE:	2:1
			SHEET 1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/20	600/20	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等	III/3	/	/
绝缘/Pollution Degree			
额定电压/电涌/Rated Voltage(V)/Current(A)	800/24	/	/
额定脉冲电压(V)/Rate Impulse Voltage(KV)	8.0	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm² /AWG)	0.2~2.5/28~12(Sol)		
厚度/Pitch(mm)/线数范围/Poles	10.00		
剥线长度/Stripping length(mm)	8~9		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:			
PANTONE / RAL	/		

DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司