



公差 (mm)		公差 (mm)	
General	tolerances	General	tolerances
0	>3	>6	>10
~	~	~	~
3	~	10	~
~	~	18	~
~	~	30	~
~	~	50	~
~	~	80	~
~	~	120	~
~	~	180	~
~	~	250	~
~	~	315	~
~	~	400	~
~	~	500	~
~	~	>500	~
~	~	>500	~
±Z	±Z	±Z	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
4	Housing1	PC	UL94V-0
3	Screw cap	Copper alloy	
2	Pin	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:		UL 标准/UL Standard:
额定电压/Rated Voltage(V)	Current(A)	300/8
IEC 标准/IEC Standard:		
过压类别/Overvoltage Category/污染等级/Pollution Degree		II/2
额定电压/电压/Rated Voltage(V)/Current(A)		250/7
额定脉冲电压(KV)/Rate Impulse Voltage(kV)		2.5
间距/Pitch (mm)/线数范围/Poles		3.81/N=02~22P
使用温度范围/Operating temperature(°C)		-40~+105
符合RoHS环保要求/Conform to RoHS		Yes

MATERIAL: SURFACE:
 MAT NO.: /
 STATUS: /
 APPD: Ian CHH 2020.05.25
 CHKD: YU JZh 2020.05.25
 DRAFT: Li Zh 2020.05.25
DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
 宁波高松电子有限公司

NAME: 15EDGRM-LD-3.81-XXP-1Y-00A(H)
 DRAWING NO.: 10002257
 TYPE: CUSTOMER DRAWING

REV	ECN	DESCRIPTION	DRAFT	DATE	SIZE	SCALE	REV	TO
1					A4	2.5:1	1/1	TO