



公差/General tolerances(mm)		0.1/10
0	>3	~
~	>6	~
3	>10	~
~	>18	~
6	>30	~
10	>50	~
18	>80	~
30	>120	~
50	>180	~
80	>250	~
120	>315	~
180	>400	~
250	>500	~
315	>500	~
400	>500	~
500	>500	~
±0.12	±0.18	±0.22
±0.22	±0.26	±0.31
±0.31	±0.37	±0.51
±0.51	±0.80	±0.93
±1.05	±1.19	±1.50
±2.20	±2.50	±2.50
#Z	#Z	#Z

ITEM	NAME OF PART	MATERIAL	NOTES
1	WFA6		
间距/Pitch(mm)/线数范围/Poles: 5.25/01P			
使用温度范围/Operating temperature(°C): -40~+105			
符合RoHS环保要求/Conform to RoHS: Yes			
SURFACE:			
MATERIAL:			
MAT NO.: /			
STATUS: /			
APPD: Li GL 2020.06.06			
CHKD: Mdo J 2020.06.06			
DRAFT: Feng X 2020.05.23			
DRAWING NO.: WFA6-C01			
NAME: DEGSON 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD			
TYPE: CUSTOMER DRAWING			
SCALE: 4:1			
REV: TO			
SHEET: 1/1			

REV	ECN	DESCRIPTION	DRAFT	DATE