



公差/General tolerance(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	3	6	10	18	30	50	80	120	180	250	315	400	500	<math>\leq 500</math>
±0.12/±0.18/±0.22/±0.26/±0.31/±0.37/±0.57/±0.80/±0.93/±1.05/±1.15/±1.60/±2.20/±2.50														±2

UL 标准/UL Standard:	B	C	D
UL 标准/UL Standard:	B	C	D
EC 标准/IEC Standard:	III/3	III/2	II/2
额定电压/电涌/Rated Voltage(V)/Current(A)	630/41	630/41	1000/41
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6	6	6
间距/Pitch(mm)/线数范围/Poles	7.62/N=02~12P		
使用温度范围/Operating temperature(°C)	-40~+120		
符合RoHS环保要求/Conform to RoHS	Yes		

4	Nut	Steel	M3/Zn Plated
3	Pin header	Copper	Sn plated
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

MATERIAL:	/
MAT NO.:	/
STATUS:	/
APPD:	/
CHKD:	/
NAME:	宁波高松电子有限公司
	NINGBO DEGSON ELECTRICAL CO., LTD

5EDGRHM-7.62-XXP-1Y-00A(H)

DRFT:	Cen/MZ	2020.06.09	DRAWING NO.:	5EDGRHM-7.62-C01
TYPE:	CUSTOMER DRAWING	SCALE: 1.5:1	REV	T0
SIZE:	A4	(mm)	SHEET	1/1