



公差/差 (General Tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±Z	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
6	Housing3	PA66	UL94V-0
5	Spring	Stainless steel	/
4	Pin	Copper	Sn plated
3	Cover	PA66	UL94V-0
2	Housing2	PA66	UL94V-0
1	Housing1	PA66	UL94V-0

UL 标准 /UL Standard:	B	C	D
额定电压/电压 (Rated Voltage(V))/Current(A)	300/15	/	300/10
IEC 标准 /IEC Standard:			
过压类别 /Overvoltage Category/污染等级	III/3	III/2	II/2
额定电压/电压 (Rated Voltage(V))/Current(A)	/	320/20	/
额定脉冲电压 (KV)/Rate Impulse Voltage(KV)	/	4	/
线径范围 (硬导线/软线) /Wire Range(rigid and flexible)(mm² /AWG)	0.2~2.5/22~14		
间距/Pitch (mm) /线径范围/Poles	5.08 /N=02~24P		
使用温度范围 /Operating Temperature(°C)	-40~+105		
符合RoHS要求 /Conform to RoHS	Yes		

MATERIAL: /
 MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /
 DFT: CenX 2020.06.16
 DRAWING NO.: 8EDGKRC-5.08-C02
 TYPE: CUSTOMER DRAWING
 SCALE: 2:1
 SHEET 1/1

DEGSON® 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

REV	ECN	DESCRIPTION	DFT	DATE