



公差等级/General Tolerances(mm)		公差等级/General Tolerances(mm)										公差等级/General Tolerances(mm)	
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	IT7

MATERIAL: /		SURFACE: /	
MAT NO.:	/	NINGBO DEGSON ELECTRICAL CO., LTD	
STATUS:	/	DRAWING NO.: D-DS10-C01	
APPD: Li GL	2020.06.01	NAME: D-DS10-01P-1Y-00A(H)	
CHKD: Moo J	2020.06.01	DRAWING NO.: D-DS10-C01	
DRAFT: Wang LX	2020.06.01	TYPE: CUSTOMER DRAWING	
REV	ECN	DESCRIPTION	DRAFT
1	2	3	4
1/1	1/1	1/1	1/1

ITEM	NAME OF PART	MATERIAL	NOTES
1	Cover	PA66	UL94V-0
使用温度范围/Operating temperature(°C) -40~+105			
符合RoHS环保要求/Conform to RoHS Yes			
标准颜色编号/Standard color number: PANTONE / RAL /			

宁波高松电子有限公司  
NINGBO DEGSON ELECTRICAL CO., LTD

D-DS10-01P-1Y-00A(H)

DRAWING NO.: D-DS10-C01

TYPE: CUSTOMER DRAWING

SCALE: 1:1

REV: 1/1

T0-3

SHEET 1/1