



精度等级/General	tolerance/(mm)	0.1/10
0	>3	~
3	~ 6	~
6	10	~
10	18	~
30	30	~
50	50	~
80	80	~
120	120	~
180	180	~
250	250	~
315	315	~
400	400	~
500	500	~
~	~	~
±Z	±Z	±Z
公差/Pitch (mm)	公差/Pitch (mm)	公差/Pitch (mm)
±0.12	±0.18	±0.22
±0.26	±0.31	±0.37
±0.57	±0.80	±0.93
±1.05	±1.15	±1.60
±2.20	±2.20	±2.50
3.50/N-02	~10P	~10P
使用温度范围/Operating temperature(°C)		
符合RoHS环保要求/Conform to RoHS		
Yes		

ITEM	NAME OF PART	MATERIAL	NOTES
3	Bridgeware	Copper	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

MATERIAL: / SURFACE: /

MAT NO.:

STATUS:

APPD: Li GL 2020.06.04

CHKD: Miao J 2020.06.04

DRAFT:ZhengQG 2020.06.04

宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO.,LTD

DFB1.5-XXP-1Y-00A(H)

DRAWING NO.: DFB1.5-C01

TYPE: CUSTOMER DRAWING

SCALE: 5:1

REV	ECN	DESCRIPTION	DRAFT	DATE	REV	ECN	DESCRIPTION	DRAFT	DATE