



公差/General		公差/General (mm)											公差/General
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/100	600/100	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/特类等	III/3	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/76	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(N·m/Lb.in)	M5, 2.5/27		
线径范围(裸线/带绝缘)/Wire Range(rigid and flexible)(mm² /AWG)	1.5~2.5/1.4~3(Str)		
厚度/Pitch(mm)	12.0		
剥线长度/Stripping length(mm)	12~13		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:	/		
PANTONE / RAL	/		

MATERIAL: /

MAT NO.: /

STATUS: /

APPD: LI GL 2020.05.25

CHKD: Moo J 2020.05.25

DRT:Wmg LX 2020.05.25

DEGSON® 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: DC16-01P-1Y-00A(H)

DRAWING NO.: DC16-C01

TYPE: CUSTOMER DRAWING SCALE: 1:1 SHEET 1/1

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cage	Steel	Zn Plated
3	Current carrier	Copper	Sn Plated
2	Screw	Steel	M5\Zn Plated
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				