




8.0

公差等级/General Tolerances(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1/10
	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.05	±1.15	±1.60	±2.20	±2.50		



4	Cage	Steel	Zn Plated
3	Current carrier	Copper	Sn Plated
2	Screw	Steel	M4\Zn Plated
1	Housing	PA66	UL94V-0

ITEM	NAME OF PART	MATERIAL	NOTES
1			
2			
3			

MATERIAL: /	SURFACE: /
MAT NO.: /	
STATUS: /	
APPD: Li GL 2020.05.15	NAME: <b>DEGSON</b> 宁波高松电子有限公司
CHKD: Moo J 2020.05.15	<b>NINGBO DEGSON ELECTRICAL CO., LTD</b>
DRT:Wong LX 2020.05.15	DC6-01P-1Y-00A(H)
DRAWING NO.: DC6-C01	
TYPE: CUSTOMER DRAWING	
SCALE: 2:1	
REV TO-5	
1/1	

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/50	/	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/特类等	III/3	/	/
级/Pollution Degree			
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/41	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(N·m/Lb.in)	M4, 1.54/14		
线径范围(裸线和镀层)/Wire Range(rigid and flexible)(mm²/AWG)	0.5~6/22~8		
厚度/Pitch(mm)	8.0		
剥线长度/Stripping length(mm)	10~12		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:			
PANTONE / RAL	/		