



公差/General Tolerances(mm)		公差/General Tolerances(mm)										公差/General Tolerances(mm)	
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1.0
~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
3	Current carrier	Copper	Sn Plated
2	Spring	Stainless steel	
1	Housing	PAG6	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

MATERIAL: /	SURFACE: /
MAT NO.: /	
STATUS: /	
APPD: Li GL 2020.05.30	NAME: DEGSON 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD
CHKD: Moo J 2020.05.30	WS1.5-01P-1Y-00A(H)
DRAFT: ZhengQG 2020.05.16	DRAWING NO.: WS1.5-C01
SIZE: A4	TYPE: CUSTOMER DRAWING
SCALE: 2:1	SCALE: 2:1
	SHEET 1/1

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	600/10	600/10	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级	III/3	/	/
绝缘/Pollution Degree	/	/	/
额定电压/电涌/Rated Voltage(V)/Current(A)	800/18	/	/
额定冲击电压(RV)/Rate Impulse Voltage(KV)	8.0		
线径范围(硬线/软线)/Wire Range(rigid and flexible)(mm² /AWG)	0.2~1.5/28~16		
厚度/Pitch(mm)	4.0		
剥线长度/Stripping length(mm)	12~13		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number:			
PANTONE / RAL	/		