



公差/差 (General Tolerances)(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±7	±7

6	Top housing	PA66	UL94V-0
5	Spring	Stainless steel	/
4	Pin	Copper	Sn plated
3	Cover	PA66	UL94V-0
2	Side housing	PA66	UL94V-0
1	Housing1	PA66	UL94V-0

UL 标准 /UL Standard:	B	C	D
额定电压/电涌 /Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准 /IEC Standard:	B	C	D
过压类别 /Overvoltage Category/ 污染等级 /Pollution Degree	III/3	III/2	II/2
额定电压/电涌 /Rated Voltage(V)/Current(A)	/	320/20	/
额定冲击电压 (KV) /Rate Impulse Voltage(KV)	/	4	/
线径范围 (硬线和软线) /Wire Range(rigid and flexible)(mm ² /AWG)	0.2~2.5/22~14		
间距 /Pitch(mm) /线径范围 /Poles	5.08/N=02~24P		
剥线长度 /Stripping length(mm)	9~10		
使用温度范围 /Operating temperature(°C)	-40~+105		
符合RoHS环保要求 /Conform to RoHS	Yes		
标准颜色编号 /Standard color number:	PANTONE 7534u		

MATERIAL: /
 SURFACE: /
 MAT NO.: /
 STATUS: /
 APPD: /
 CHKD: /

NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**
8EDGKRB-5.08-XXP-11-01A(H)

DRAWING NO.: 8EDGKRB-5.08-C02
 TYPE: CUSTOMER DRAWING
 SCALE: 2:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE
(T1)	18-0139	Change drawing	CZ	2018.05.24