



公差/General Tolerances(mm)		公差/General Tolerances(mm)	
0	>3	>6	>18
~	~	~	~
3	6	10	18
~	~	~	~
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±1.05	±1.15	±1.60	±2.20
±2.50	±2.50	±2.50	±2.50
~	~	~	~
0.1/10	~	~	~
±2	~	~	~

ITEM	NAME OF PART	MATERIAL	NOTES
4	Pin Fastener	Steel	M4/Ni Plated
3	Pin header	Copper	Sn Plated
2	Screw	Steel	M4/Ni Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:		B	C	D
额定电压/Rated Voltage(V)	Current(A)	600/30	600/30	600/5
IEC 标准/IEC Standard:				
过压类别/Overvoltage Category/污染等	级/ Pollution Degree	III/3	III/2	II/2
额定电压/Rated Voltage(V)	Current(A)	1000/32	1000/32	1000/32
额定脉冲电压/Rate Impulse Voltage(KV)	10	10	10	10
额定扭矩/Torque Tightening(N·m/Lb·in)	M4, 1.80/15.94			
线材范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	4.0/22~10			
可焊/Pitch(mm)/线数范围/Poles	11.0/N=02~25P			
剥线长度/Stripping length(mm)	9			
使用温度范围/Operating temperature(°C)	-40~+105			
符合RoHS环保要求/Conform to RoHS	Yes			

MATERIAL: / SURFACE: /

MAI NO.: /

STATUS: /

APPD: /

CHKD: /

DRAFT: CenMZ 2020.05.27

DRAWING NO.: DG66-C09

REV	ECN	DESCRIPTION	DRAFT	DATE

TYPE: CUSTOMER DRAWING SCALE: 1:1 SHEET 1/1

NAME: **DEGSON** 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: **DG66-DA-XXP-1Y-00A(H)**