



Pitch range in mm		Nominal dimension range							
In mm		In mm							
over	over	over	over	over	over	over	over	over	over
to	to	to	to	to	to	to	to	to	to
6	10	10	24	30	60	100	150	150	150
10	10	10	24	30	60	100	150	150	150

3	Screw	Steel	Ni Plated	
2	Pin header	Copper alloy	Sn Plated	
1	Housing	PA66	UL94V-0	
ITEM	NAME OF PART	MATERIAL	NOTES	
UL 标准/UL Standard:	B	C	D	
额定电压/Rated Voltage(V)	300/25	/	300/70	
EC 标准/IEC Standard:	III/3	III/2	II/2	
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/3	III/2	II/2	
额定电压/电流/Rated Voltage(V)/Current(A)	500/32	600/32	1000/32	
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6	6	6	
螺丝扭矩/Torque Tightening(N.m/Lb.in)	M4: 1.2/10.53			
线径范围(硬线和软线)/ Wire Range(rigid and flexible)(mm²/ AWG)	0.34~4/22~12			
间距/Pitch(mm)/线数范围/Poles	9.50/N=02~26P			
剥线长度/Stripping length(mm)	8			
使用温度范围/Operating temperature(°C)	-40~+105			
符合RoHS环保要求/Conform to RoHS	Yes			

MATERIAL: /

MAT NO.: /

STATUS: work

APPD: /

CHKD: /

DRAFT: XieZhp 2020.05.25

DRAWING NO.: DG45H-C03

TYPE: CUSTOMER DRAWING

SCALE: 1:1 SHEET 1/1

REV	ECN	DESCRIPTION	DRAFT	DATE

D C B A

1 2 3 4 5 6

D C B A