



公差/General Tolerances(mm)		公差/General Tolerances(mm)	
0	>3	>10	>30
~	>6	>18	>50
~	>10	>30	>80
~	18	50	80
~	30	80	120
~	50	120	180
~	80	180	250
~	120	250	315
~	180	315	400
~	250	315	400
~	315	400	500
~	400	500	500
~	500	500	500
±0.12	±0.18	±0.22	±0.26
±0.31	±0.37	±0.57	±0.80
±0.93	±1.05	±1.15	±1.60
±2.20	±2.50		

UL 标准/UL Standard:	B	C	D
额定电压/电压/Rated Voltage(V)/Current(A)	600/150	/	/
EC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	/	/
额定电压/电流/Rated Voltage(V)/Current(A)	1000/125	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
螺丝扭矩/Torque Tightening(N·m/Lb·in)	M6: 2.5/22.15	/	/
导线范围(铜线和铝线)/Wire Range(rigid and flexible)(mm²/AWG)	1.5~35/14~1/0	/	/
间距/Pitch(mm)/线圈范围/Poles	16.20	/	/
剥线长度/Stripping length(mm)	18~19	/	/
使用温度范围/Operating temperature(°C)	-40~+105	/	/
符合RoHS环保要求/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:	/	/	/
PANTONE / RAL	/	/	/

MATERIAL: SURFACE: /

MAT NO.: /
STATUS: /
NAME: **DEGSON** 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

APPD: Li GL 2020.06.04
CHKD: Mao J 2020.06.04
NAME: **PC35-01P-1Y-105A(H)**

DRAWING NO.: PC35-C25
DRAFT: Feng X 2020.05.30
TYPE: CUSTOMER DRAWING
SCALE: 1:1 SHEET 1/1

ITEM	NAME OF PART	MATERIAL	NOTES	REV	ECN	DESCRIPTION	DRAFT	DATE
1	Housing1	PA66	UL94V-0					
2	Screw	Steel	M6/Zn Plated					
3	Current Carrier	Copper	Sn Plated					
4	Cage	Steel	M6/Zn Plated					
5	Housing2	PA66	UL94V-0					

1 2 3 4 5 6