

未注公差/General tolerances(mm)										ϕ			
0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	$\frac{\square}{\square}$
3	6	10	18	30	50	80	120	180	250	315	400	500	$\pm Z$
± 0.12	± 0.18	± 0.22	± 0.26	± 0.31	± 0.37	± 0.57	± 0.80	± 0.93	± 1.05	± 1.19	± 1.50	± 2.20	± 2.50

UL 标准/UL Standard:												
额定电压/电流/Rated Voltage(V)/Current(A)	B	C	D									
300/30	/	/	300/10									
EC 标准/EC Standard:												
过压类别/Overvoltage Category/污秽等级/Pollution Degree	III/3	/	/									
额定电压/电流/Rated Voltage(V)/Current(A)	500/32	/	/									
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	6.0	/	/									
螺栓扭矩/Torque Tightening(N·m/Lb·in)	M3, 0.5/4.43											
绞合范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~4.0/26~10											
间距/Pitch(mm)	6.20											
剥线长度/Stripping length(mm)	7-8											
使用温度范围/Operating temperature(°C)	-40~+105											
符合RoHS环保要求/Conform to RoHS	Yes											
标准颜色编号/Standard color number:	/											
PANTONE / RAL	/											
SURFACE:												
MATERIAL:												
MAT NO.:												
NINGBO DEGSON ELECTRICAL CO., LTD												
APPD:												
NAME:												
CHKD:												
DRAWING NO.:												
DRAFT:												
REV	ECN	DESCRIPTION	DRAFT	DATE			TYPE:	SCALE:	REV			
1	2	3	4	5					SHEET			