



公差/General Tolerances(mm)	
0	>3
~	>6
3	>10
6	>18
10	>30
18	>50
30	>80
50	>120
80	>180
120	>250
180	>315
250	>400
315	>500
400	>500
500	>500
±0.12	±0.18
±0.22	±0.26
±0.31	±0.37
±0.57	±0.80
±0.80	±0.93
±1.05	±1.15
±1.60	±2.20
±2.50	±2.50
0.1/10	±2

5	Ground contact		
4	Screw	Copper Alloy	M3\Ni Plated
3	Cage	Copper Alloy	M3\Ni Plated
2	Housing	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电压/ Rated Voltage(V)/Current(A)	/	/	/
EC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污染等级/ Pollution Degree	III/3	/	/
额定电压/电压/ Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.5/4.43	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm²/AWG)	0.2~4.0/24~10	/	/
前距/Pitch(mm)	6.2	/	/
剥线长度/Stripping length(mm)	6~7	/	/
使用温度范围/Operating temperature(°C)	-40~+105	/	/
符合RoHS环保要求/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:		/	/
PANTONE / RAL		/	/

SURFACE:

MATERIAL:

MAT NO.:

STATUS:

APPD: LI GL 2020.04.03

CHKD: Mao J 2020.04.03

DRAFT: Expsany 2005.11.14

DEGSON® 宁波高松电子有限公司
NINGBO DEGSON ELECTRICAL CO., LTD

NAME: PC4-PE-01P-1Y-00A(H)

DRAWING NO.: PC4-PE-C01

TYPE: CUSTOMER DRAWING

SCALE: 2:1 SHEET 1/1

REV ECN DESCRIPTION DRAFT DATE

SIZE: A4

mm

inch

REV T1