



公差/General		公差/General (mm)										公差/General	
0	>3	>5	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	0.1/1.0
~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

ITEM	NAME OF PART	MATERIAL	NOTES
6	Screw	Steel	M6\Zn Plated
5	Cage	Steel	Zn Plated
4	Current carrier	Copper	Sn Plated
3	Cover	PA66	UL94V-0
2	Grounding body	Copper alloy	Sn Plated
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRAFT	DATE
1				
2				
3				

MATERIAL: /	SURFACE: /
MAT NO.: /	
STATUS: /	
APPD: Li GL 2020.05.25	NAME: DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD
CHKD: Moo J 2020.05.25	DC35-PE-01P-1C-00A(H)
DRAFT:Wmg LX 2020.05.25	DRAWING NO.: DC35-PE-C01
TYPE: CUSTOMER DRAWING	SCALE: 1:1
	REV TO-2
	1/1 SHEET

UL 标准/UL Standard:	B	C	D
额定电压/Rated Voltage(V)/Current(A)	/	/	/
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/特类等	III/3	/	/
级/Pollution Degree	/	/	/
额定电压/电压/Rated Voltage(V)/Current(A)	/	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
额定扭矩/Torque Tightening(N.m/Lb.in)	M6: 3.5/31	/	/
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm² /AWG)	14~2/2.5~35	/	/
厚度/Pitch(mm)	16.0	/	/
剥线长度/Stripping length(mm)	14~16	/	/
使用温度范围/Operating Temperature(°C)	-40~+105	/	/
符合RoHS要求/Conform to RoHS	Yes	/	/
标准颜色编号/Standard color number:	/	/	/
PANTONE / RAL	/	/	/