



公差等级/General tolerances(mm)		0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50			

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/20	/	/
EC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	1000/24	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8.0	/	/
螺丝扭矩/Torque Tightening(N·m/Lb·in)	M2.5, 0.4/4.43		
绞合范围(硬线和软线)/Wire Range(rigid and flexible)(mm <sup>2</sup> /AWG)	0.2~2.5&4(Sol)/22~12		
间距/Pitch(mm)	5.10		
剥线长度/Stripping length(mm)	10		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

MATERIAL: / SURFACE: /

MAT NO.: / STATUS: /  
 APPD: LiGL 2020.04.11 NAME: **DEGSON** 宁波高松电子有限公司  
 NINGBO DEGSON ELECTRICAL CO., LTD  
 CHKD: MoEK 2020.04.11

DC2.5-TW-01P-1Y-00A(H)

DRAWING NO.: DC2.5-TW-001 TYPE: CUSTOMER DRAWING SCALE: 2:1 SHEET 1/1  
 DRAFT: FengX 2019.09.24

ITEM	NAME OF PART	MATERIAL	NOTES	REV	ECN	DESCRIPTION	DRAFT	DATE
4	Screw	Steel	Zn Plated					
3	Cage	Steel	Zn Plated					
2	Current Carrier	Copper	Sn Plated					
1	Housing	PA66	UL94V-0					

1 2 3 4 5 6