



公差等级/General	tolerance(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>280	>315	>400	>500	0.1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2.50	±Z	±Z

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cage	Copper Alloy	M3.5/Ni Plated
3	Pin Header	Copper	Sn Plated
2	Screw	Steel	M3.5/Zn Plated
1	Housing	PA66	UL94V-0

UL 标准/UL Standard:	B	C	D
额定电压/电涌/Rated Voltage(V)/Current(A)	300/30	300/30	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污秽等级/Pollution Degree	II/2	III/2	III/3
额定电压/电涌/Rated Voltage(V)/Current(A)	1000/32	1000/32	690/32
额定脉冲电压(kV)/Rate Impulse Voltage(kV)	6.0		
拧紧扭矩/Torque Tightening(N·m/Lb·in)	M3.5: 0.8/7.02		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(mm ² /AWG)	0.2~4/30~10		
间距/Pitch(mm)/线数范围/Poles	9.52/N=02~12P		
引线长度/Stripping length(mm)	8~9		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS标准/Conform to RoHS	Yes		

MATERIAL: /
 SURFACE: /
 MAT NO.: /
 STATUS: /

APPD: Lan CHH 2020.05.18
 CHKD: Yu JZh 2020.05.18
 DRT: Joy.z 2014.12.30

NAME: DG636S-9.52-XXP-1Y-00A(H)
 DRAWING NO.: DG636S-9.52-C01
 TYPE: CUSTOMER DRAWING
 SCALE: 2:1
 SHEET 1/1

REV	ECN	DESCRIPTION	DRT	DATE
1				
2				
3				
4				